

Datasheet Generated On: 2022-03-10 Data Last Changed On: 2022-03-10



REACH

# EPDM 60 compound 559679

Blue EPDM moulded sheet, for cut parts used in food industry.

# Characteristics

- Colour: Blue
- Temp. resistance low: -25 °C
- Temp. resistance high: 100 °C
- Hardness tolerance: -5/+5

### **Approval & Compliancy details**

For Food & Beverage compliances, see Declaration of Compliance for typical application of the compound.

- Bisphenol A free
- CH-817.023.21
- EC1935:2004
- Phtalates free
- REACH
- RoHS
- TSCA

#### **Products**

Sheets (moulded)

# **Table: Physical Properties**

Property	Value	Unit
Hardness Shore A - Slab	58	
Hardness - Test standard	ISO7619	
Compression set - Slab	30	%
Compression set - Duration @ temperature	22 hours at 70°C	
Compression set Test standard	ISO815	
Elongation at break	550	%
Elongation at break - Test standard	ISO37	
Tensile strength	12	MPa
Tensile strength - Test standard	ISO37	

Disclaimer: The datasheet shows typical values and is verified against internal material specifications. The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete. The information provided is not intended to be used without advice. ERIKS shall never be liable for damage resulting from the use of the information provided.