



Taper Lock® Bushes

Taper Lock Four Hole Bush

Simple, Universal Solution

1008 Metric Bore

Screw Tightening Torque	Screw Quantity	Screw Size	Hex Socket Size	Large End Diameter	Bush Length	Approximate Mass
Nm		BSW	mm	mm	mm	Kg
5.6	2	1/4"	3	35	22.3	0.1

Fenner Reference	Bore Diameter	Keyway Width	Keyway Depth	Shallow Keyway Depth
	mm	mm	mm	mm
029A0009	9	3	1.4	-
029A0010	10	3	1.4	-
029A0011	11	4	1.8	-
029A0012	12	4	1.8	-
029A0014	14	5	2.3	-
029A0015	15	5	2.3	-
029A0016	16	5	2.3	-
029A0018	18	6	2.8	-
029A0019	19	6	2.8	-
029A0020	20	6	2.8	-
029A0022	22	6	2.8	-
029A0024*	24	8	3.3	1.3
029A0025*	25	8	3.3	1.3



Keyways are British Standard Metric BS 4235: Part 1: 1972 DIN 6885 and conform to ISO recommendations with the exception of those marked* which are shallower. Where a key is to be used it should be parallel and side fitting, with top clearance. Depth of keyway is measured at the CENTRE.

Fenner®

Reliable | Trusted | Connected