



Taper Lock® Bushes

Taper Lock Four Hole Bush Simple, Universal Solution

1108 Metric Bore

Screw Tightening Torque	Screw Quantity	Screw Size	Hex Socket Size	Large End Diameter	Bush Length	Approximate Mass
Nm		BSW	mm	mm	mm	Kg
2.6	2	1/4"	3	38	22.3	0.1

Fenner Reference	Bore Diameter	Keyway Width	Keyway Depth	Shallow Keyway Depth
	mm	mm	mm	mm
029B0009	9	3	1.4	-
029B0010	10	3	1.4	-
029B0011	11	4	1.8	-
029B0012	12	4	1.8	-
029B0014	14	5	2.3	-
029B0015	15	5	2.3	-
029B0016	16	5	2.3	-
029B0018	18	6	2.8	-
029B0019	19	6	2.8	-
029B0020	20	6	2.8	-
029B0022	22	6	2.8	-
029B0024	24	8	3.3	1.3
029B0025	25	8	3.3	1.3
029B0028*	28	8	3.3	1.3



Keyways are British Standard Metric BS 4235: Part 1: 1972 DIN 6885 and conform to ISO recommendations with the exception of those marked* which are shallower. Where a key is to be used it should be parallel and side fitting, with top clearance. Depth of keyway is measured at the CENTRE.

Bold indicates bushes made of steel or ductile iron.

Fenner®

Reliable | Trusted | Connected