



Taper Lock® Bushes

Taper Lock Four Hole Bush Simple, Universal Solution

1210 Metric Bore

Screw Tightening Torque	Screw Quantity	Screw Size	Hex Socket Size	Large End Diameter	Bush Length	Approximate Mass
Nm		BSW	mm	mm	mm	Kg
20	2	3/8"	5	47.5	25.4	0.2

Fenner Reference	Bore Diameter	Keyway Width	Keyway Depth	Shallow Keyway Depth
	mm	mm	mm	mm
029C0011	11	4	1.8	-
029C0012	12	4	1.8	-
029C0014	14	5	2.3	-
029C0015	15	5	2.3	-
029C0016	16	5	2.3	-
029C0018	18	6	2.8	-
029C0019	19	6	2.8	-
029C0020	20	6	2.8	-
029C0022	22	6	2.8	-
029C0024	24	8	3.3	1.3
029C0025	25	8	3.3	1.3
029C0028	28	8	3.3	1.3
029C0030	30	8	3.3	-
029C0032	32	10	3.3	-



Keyways are British Standard Metric BS 4235: Part 1: 1972 DIN 6885 and conform to ISO recommendations with the exception of those marked* which are shallower. Where a key is to be used it should be parallel and side fitting, with top clearance. Depth of keyway is measured at the CENTRE.

Fenner®

Reliable | Trusted | Connected