



# Taper Lock® Bushes

## Taper Lock Four Hole Bush

Simple, Universal Solution

### 1610 Imperial Bore

Screw Tightening Torque	Screw Quantity	Screw Size	Hex Socket Size	Large End Diameter	Bush Length	Approximate Mass
Nm		BSW	mm	mm	mm	Kg
20	2	3/8"	5	57	25.4	0.3

Fenner Reference	Bore Diameter	Keyway Width	Keyway Depth	Shallow Keyway Depth
	inch	inch	inch	inch
019G0008	0.5	0.125	0.06	-
019G0010	0.625	0.187	0.09	-
019G0012	0.75	0.187	0.09	-
019G0014	0.875	0.25	0.12	-
019G0100	1	0.25	0.12	0.052
019G0102	1.125	0.312	0.11	0.064
019G0104	1.25	0.312	0.11	-
019G0106	1.375	0.375	0.11	-
019G0108	1.5	0.375	0.11	-
019G0110	1.625	0.437	0.13	0.103



All Keyways are parallel and to British Standard 46: Part 1: 1958, with the exception of those marked\* which are shallower. Where a key is to be used it should be side fitting, with top clearance. Depth of keyway is measured at the CENTRE.

# Fenner®

Reliable | Trusted | Connected