



Taper Lock® Bushes

Taper Lock Four Hole Bush

Simple, Universal Solution

1610 Metric Bore

Screw Tightening Torque	Screw Quantity	Screw Size	Hex Socket Size	Large End Diameter	Bush Length	Approximate Mass
Nm		BSW	mm	mm	mm	Kg
20	2	3/8"	5	57	25.4	0.3

Fenner Reference	Bore Diameter	Keyway Width	Keyway Depth	Shallow Keyway Depth
	mm	mm	mm	mm
029G0014	14	5	2.3	-
029G0015	15	5	2.3	-
029G0016	16	5	2.3	-
029G0018	18	6	2.8	-
029G0019	19	6	2.8	-
029G0020	20	6	2.8	-
029G0022	22	6	2.8	-
029G0024	24	8	3.3	1.3
029G0025	25	8	3.3	1.3
029G0028	28	8	3.3	1.3
029G0030	30	8	3.3	-
029G0032	32	10	3.3	-
029G0035	35	10	3.3	-
029G0038	38	10	3.3	-
029G0040	40	12	3.3	-
029G0042*	42	12	3.3	2.2



Keyways are British Standard Metric BS 4235: Part 1: 1972 DIN 6885 and conform to ISO recommendations with the exception of those marked* which are shallower. Where a key is to be used it should be parallel and side fitting, with top clearance. Depth of keyway is measured at the CENTRE.

Bold indicates bushes made of steel or ductile iron.

Fenner®

Reliable | Trusted | Connected