



Taper Lock® Bushes

Taper Lock Four Hole Bush

Simple, Universal Solution

2012 Metric Bore

Screw Tightening Torque	Screw Quantity	Screw Size	Hex Socket Size	Large End Diameter	Bush Length	Approximate Mass
Nm		BSW	mm	mm	mm	Kg
30	2	7/16"	6	70	38.1	0.7

Fenner Reference	Bore Diameter	Keyway Width	Keyway Depth	Shallow Keyway Depth
	mm	mm	mm	mm
029K0014	14	5	2.3	-
029K0015	15	5	2.3	-
029K0016	16	5	2.3	-
029K0018	18	6	2.8	-
029K0019	19	6	2.8	-
029K0020	20	6	2.8	-
029K0022	22	6	2.8	-
029K0024	24	8	3.3	1.3
029K0025	25	8	3.3	1.3
029K0028	28	8	3.3	1.3
029K0030	30	8	3.3	-
029K0032	32	10	3.3	-
029K0035	35	10	3.3	-
029K0038	38	10	3.3	-
029K0040	40	12	3.3	-
029K0042	42	12	3.3	2.2
029K0045	45	14	3.8	-
029K0048	48	14	3.8	-
029K0050	50	14	3.8	-



Keyways are British Standard Metric BS 4235: Part 1: 1972 DIN 6885 and conform to ISO recommendations with the exception of those marked* which are shallower. Where a key is to be used it should be parallel and side fitting, with top clearance. Depth of keyway is measured at the CENTRE.

Fenner®

Reliable | Trusted | Connected