



Taper Lock® Bushes

Taper Lock Four Hole Bush

Simple, Universal Solution

2517 Metric Bore

Screw Tightening Torque	Screw Quantity	Screw Size	Hex Socket Size	Large End Diameter	Bush Length	Approximate Mass
Nm		BSW	mm	mm	mm	Kg
50	2	1/2"	6	85.5	44.5	1.5

Fenner Reference	Bore Diameter	Keyway Width	Keyway Depth	Shallow Keyway Depth
	mm	mm	mm	mm
029M0016	16	5	2.3	-
029M0018	18	6	2.8	-
029M0019	19	6	2.8	-
029M0020	20	6	2.8	-
029M0022	22	6	2.8	-
029M0024	24	8	3.3	1.3
029M0025	25	8	3.3	1.3
029M0028	28	8	3.3	1.3
029M0030	30	8	3.3	-
029M0032	32	10	3.3	-
029M0035	35	10	3.3	-
029M0038	38	10	3.3	-
029M0040	40	12	3.3	-
029M0042	42	12	3.3	2.2
029M0045	45	14	3.8	-
029M0048	48	14	3.8	-
029M0050	50	14	3.8	-
029M0055	55	16	4.3	-
029M0060	60	18	4.4	-



Keyways are British Standard Metric BS 4235: Part 1: 1972 DIN 6885 and conform to ISO recommendations with the exception of those marked* which are shallower. Where a key is to be used it should be parallel and side fitting, with top clearance. Depth of keyway is measured at the CENTRE.

Fenner®

Reliable | Trusted | Connected