



# Taper Lock® Bushes

## Taper Lock Four Hole Bush

Simple, Universal Solution

### 3020 Metric Bore

Screw Tightening Torque	Screw Quantity	Screw Size	Hex Socket Size	Large End Diameter	Bush Length	Approximate Mass
Nm		BSW	mm	mm	mm	Kg
90	2	5/8"	8	108.6	50.8	2.7

Fenner Reference	Bore Diameter	Keyway Width	Keyway Depth	Shallow Keyway Depth
	mm	mm	mm	mm
029P0025	25	8	3.3	1.3
029P0028	28	8	3.3	1.3
029P0030	30	8	3.3	-
029P0032	32	10	3.3	-
029P0035	35	10	3.3	-
029P0038	38	10	3.3	-
029P0040	40	12	3.3	-
029P0042	42	12	3.3	2.2
029P0045	45	14	3.8	-
029P0048	48	14	3.8	-
029P0050	50	14	3.8	-
029P0055	55	16	4.3	-
029P0060	60	18	4.4	-
029P0065	65	18	4.4	-
029P0070	70	20	4.9	-
029P0075	75	20	4.9	-



Keyways are British Standard Metric BS 4235: Part 1: 1972 DIN 6885 and conform to ISO recommendations with the exception of those marked\* which are shallower. Where a key is to be used it should be parallel and side fitting, with top clearance. Depth of keyway is measured at the CENTRE.

# Fenner®

Reliable | Trusted | Connected