



# Taper Lock® Bushes

## Taper Lock Four Hole Bush

Simple, Universal Solution

### 3030 Metric Bore

Screw Tightening Torque	Screw Quantity	Screw Size	Hex Socket Size	Large End Diameter	Bush Length	Approximate Mass
Nm		BSW	mm	mm	mm	Kg
90	2	5/8"	8	108	76.2	3.6

Fenner Reference	Bore Diameter	Keyway Width	Keyway Depth	Shallow Keyway Depth
	mm	mm	mm	mm
029Q0035	35	10	3.3	-
029Q0038	38	10	3.3	-
029Q0040	40	12	3.3	-
029Q0042	42	12	3.3	2.2
029Q0045	45	14	3.8	-
029Q0048	48	14	3.8	-
029Q0050	50	14	3.8	-
029Q0055	55	16	4.3	-
029Q0060	60	18	4.4	-
029Q0065	65	18	4.4	-
029Q0070	70	20	4.9	-
029Q0075	75	20	4.9	-



Keyways are British Standard Metric BS 4235: Part 1: 1972 DIN 6885 and conform to ISO recommendations with the exception of those marked\* which are shallower. Where a key is to be used it should be parallel and side fitting, with top clearance. Depth of keyway is measured at the CENTRE.

# Fenner®

Reliable | Trusted | Connected