



Taper Lock® Bushes

Taper Lock Five Hole Bush

Simple, Universal Solution

3525 Metric Bore

Screw Tightening Torque	Screw Quantity	Screw Size	Hex Socket Size	Large End Diameter	Bush Length	Approximate Mass
Nm		BSW	mm	mm	mm	Kg
115	3	1/2"	10	127	63.5	3.8

Fenner Reference	Bore Diameter	Keyway Width	Keyway Depth	Shallow Keyway Depth
	mm	mm	mm	mm
029J0035	35	10	3.3	-
029J0038	38	10	3.3	-
029J0040	40	12	3.3	-
029J0042	42	12	3.3	-
029J0045	45	14	3.8	-
029J0048	48	14	3.8	-
029J0050	50	14	3.8	-
029J0055	55	16	4.3	-
029J0060	60	18	4.4	-
029J0065	65	18	4.4	-
029J0070	70	20	4.9	-
029J0075	75	20	4.9	-
029J0080	80	22	5.4	-
029J0085	85	22	5.4	-
029J0090	90	25	5.4	-
029J0095	95	25	5.4	-
029J0100*	100	28	6.4	4.4



Keyways are British Standard Metric BS 4235: Part 1: 1972 DIN 6885 and conform to ISO recommendations with the exception of those marked* which are shallower. Where a key is to be used it should be parallel and side fitting, with top clearance. Depth of keyway is measured at the CENTRE.

Bold indicates bushes made of steel or ductile iron.

Fenner®

Reliable | Trusted | Connected