



Taper Lock® Bushes

Taper Lock Five Hole Bush

Simple, Universal Solution

4030 Metric Bore

Screw Tightening Torque	Screw Quantity	Screw Size	Hex Socket Size	Large End Diameter	Bush Length	Approximate Mass
Nm		BSW	mm	mm	mm	Kg
170	3	5/8"	12	146	76.2	5.6

Fenner Reference	Bore Diameter	Keyway Width	Keyway Depth	Shallow Keyway Depth
	mm	mm	mm	mm
029X0040	40	12	3.3	-
029X0042	42	12	3.3	-
029X0045	45	14	3.8	-
029X0048	48	14	3.8	-
029X0050	50	14	3.8	-
029X0055	55	16	4.3	-
029X0060	60	18	4.4	-
029X0065	65	18	4.4	-
029X0070	70	20	4.9	-
029X0075	75	20	4.9	-
029X0080	80	22	5.4	-
029X0085	85	22	5.4	-
029X0090	90	25	5.4	-
029X0095	95	25	5.4	-
029X0100	100	28	6.4	4.4
029X0105	105	28	6.4	-
029X0110	110	28	6.4	-
029X0115*	115	32	7.4	5.4



Keyways are British Standard Metric BS 4235: Part 1: 1972 DIN 6885 and conform to ISO recommendations with the exception of those marked* which are shallower. Where a key is to be used it should be parallel and side fitting, with top clearance. Depth of keyway is measured at the CENTRE.

Bold indicates bushes made of steel or ductile iron.

Fenner®

Reliable | Trusted | Connected