



Taper Lock® Bushes

Taper Lock Five Hole Bush

Simple, Universal Solution

4040 Metric Bore

Screw Tightening Torque	Screw Quantity	Screw Size	Hex Socket Size	Large End Diameter	Bush Length	Approximate Mass
Nm		BSW	mm	mm	mm	Kg
170	3	5/8"	12	146	102	7.7

Fenner Reference	Bore Diameter	Keyway Width	Keyway Depth	Shallow Keyway Depth
	mm	mm	mm	mm
029S0040	40	12	3.3	-
029S0042	42	12	3.3	-
029S0045	45	14	3.8	-
029S0048	48	14	3.8	-
029S0050	50	14	3.8	-
029S0055	55	16	4.3	-
029S0060	60	18	4.4	-
029S0065	65	18	4.4	-
029S0070	70	20	4.9	-
029S0075	75	20	4.9	-
029S0080	80	22	5.4	-
029S0085	85	22	5.4	-
029S0090	90	25	5.4	-
029S0095	95	25	5.4	-
029S0100	100	28	6.4	4.4



Keyways are British Standard Metric BS 4235: Part 1: 1972 DIN 6885 and conform to ISO recommendations with the exception of those marked* which are shallower. Where a key is to be used it should be parallel and side fitting, with top clearance. Depth of keyway is measured at the CENTRE.

Fenner®

Reliable | Trusted | Connected