



Taper Lock® Bushes

Taper Lock Five Hole Bush

Simple, Universal Solution

4535 Metric Bore

Screw Tightening Torque	Screw Quantity	Screw Size	Hex Socket Size	Large End Diameter	Bush Length	Approximate Mass
Nm		BSW	mm	mm	mm	Kg
190	3	3/4"	14	162	89	7.5

Fenner Reference	Bore Diameter	Keyway Width	Keyway Depth	Shallow Keyway Depth
	mm	mm	mm	mm
029Y0055	55	16	4.3	-
029Y0060	60	18	4.4	-
029Y0065	65	18	4.4	-
029Y0070	70	20	4.9	-
029Y0075	75	20	4.9	-
029Y0080	80	22	5.4	-
029Y0085	85	22	5.4	-
029Y0090	90	25	5.4	-
029Y0095	95	25	5.4	-
029Y0100	100	28	6.4	4.4
029Y0105	105	28	6.4	-
029Y0110	110	28	6.4	-
029Y0115	115	32	7.4	5.4
029Y0120	120	32	7.4	-
029Y0125	125	32	7.4	-



Keyways are British Standard Metric BS 4235: Part 1: 1972 DIN 6885 and conform to ISO recommendations with the exception of those marked* which are shallower. Where a key is to be used it should be parallel and side fitting, with top clearance. Depth of keyway is measured at the CENTRE.

Bold indicates bushes made of steel or ductile iron.

Fenner®

Reliable | Trusted | Connected