



# Taper Lock® Bushes

## Taper Lock Five Hole Bush

Simple, Universal Solution

### 4545 Imperial Bore

Screw Tightening Torque	Screw Quantity	Screw Size	Hex Socket Size	Large End Diameter	Bush Length	Approximate Mass
Nm		BSW	mm	mm	mm	Kg
190	3	3/4"	14	162	114	10

Fenner Reference	Bore Diameter	Keyway Width	Keyway Depth	Shallow Keyway Depth
	inch	inch	inch	inch
019T0204	2.25	0.625	0.18	-
019T0206	2.375	0.625	0.18	-
019T0208	2.5	0.625	0.18	-
019T0210	2.625	0.75	0.21	-
019T0212	2.75	0.75	0.21	-
019T0214	2.875	0.75	0.21	-
019T0300	3	0.75	0.21	-
019T0302	3.125	0.875	0.26	-
019T0304	3.25	0.875	0.26	-
019T0306	3.375	0.875	0.26	-
019T0308	3.5	0.875	0.26	-
019T0312	3.75	1	0.32	0.245
019T0400	4	1	0.32	0.155
019T0404	4.25	1.25	0.37	-
019T0408	4.5	1.25	0.37	0.255



All Keyways are parallel and to British Standard 46: Part 1: 1958, with the exception of those marked\* which are shallower. Where a key is to be used it should be side fitting, with top clearance. Depth of keyway is measured at the CENTRE.

# Fenner®

Reliable | Trusted | Connected