



Taper Lock® Bushes

Taper Lock Five Hole Bush

Simple, Universal Solution

4545 Metric Bore

| Screw Tightening Torque | Screw Quantity | Screw Size | Hex Socket Size | Large End Diameter | Bush Length | Approximate Mass |
|-------------------------|----------------|------------|-----------------|--------------------|-------------|------------------|
| Nm | | BSW | mm | mm | mm | Kg |
| 190 | 3 | 3/4" | 14 | 162 | 114 | 10 |

| Fenner Reference | Bore Diameter | Keyway Width | Keyway Depth | Shallow Keyway Depth |
|------------------|---------------|--------------|--------------|----------------------|
| | mm | mm | mm | mm |
| 029T0055 | 55 | 16 | 4.3 | - |
| 029T0060 | 60 | 18 | 4.4 | - |
| 029T0065 | 65 | 18 | 4.4 | - |
| 029T0070 | 70 | 20 | 4.9 | - |
| 029T0075 | 75 | 20 | 4.9 | - |
| 029T0080 | 80 | 22 | 5.4 | - |
| 029T0085 | 85 | 22 | 5.4 | - |
| 029T0090 | 90 | 25 | 5.4 | - |
| 029T0095 | 95 | 25 | 5.4 | - |
| 029T0100 | 100 | 28 | 6.4 | 4.4 |
| 029T0105 | 105 | 28 | 6.4 | - |
| 029T0110 | 110 | 28 | 6.4 | - |



Keyways are British Standard Metric BS 4235: Part 1: 1972 DIN 6885 and conform to ISO recommendations with the exception of those marked* which are shallower. Where a key is to be used it should be parallel and side fitting, with top clearance. Depth of keyway is measured at the CENTRE.

Fenner®

Reliable | Trusted | Connected