



# Taper Lock® Bushes

## Taper Lock Five Hole Bush

Simple, Universal Solution

### 5040 Metric Bore

Screw Tightening Torque	Screw Quantity	Screw Size	Hex Socket Size	Large End Diameter	Bush Length	Approximate Mass
Nm		BSW	mm	mm	mm	Kg
270	3	7/8"	14	178	102	11.1

Fenner Reference	Bore Diameter	Keyway Width	Keyway Depth	Shallow Keyway Depth
	mm	mm	mm	mm
029Z0070	70	20	4.9	-
029Z0075	75	20	4.9	-
029Z0080	80	22	5.4	-
029Z0085	85	22	5.4	-
029Z0090	90	25	5.4	-
029Z0095	95	25	5.4	-
029Z0100	100	28	6.4	4.4
029Z0105	105	28	6.4	-
029Z0110	110	28	6.4	-
029Z0115	115	32	7.4	5.4
029Z0120	120	32	7.4	-
029Z0125	125	32	7.4	-



Keyways are British Standard Metric BS 4235: Part 1: 1972 DIN 6885 and conform to ISO recommendations with the exception of those marked\* which are shallower. Where a key is to be used it should be parallel and side fitting, with top clearance. Depth of keyway is measured at the CENTRE.

# Fenner®

Reliable | Trusted | Connected