



# Taper Lock® Bushes

## Taper Lock Five Hole Bush

Simple, Universal Solution

### 5050 Imperial Bore

Screw Tightening Torque	Screw Quantity	Screw Size	Hex Socket Size	Large End Diameter	Bush Length	Approximate Mass
Nm		BSW	mm	mm	mm	Kg
270	3	7/8"	14	178	127	14

Fenner Reference	Bore Diameter	Keyway Width	Keyway Depth	Shallow Keyway Depth
	inch	inch	inch	inch
019U0212	2.75	0.75	0.21	-
019U0214	2.875	0.75	0.21	-
019U0300	3	0.75	0.21	-
019U0302	3.125	0.875	0.26	-
019U0304	3.25	0.875	0.26	-
019U0306	3.375	0.875	0.26	-
019U0308	3.5	0.875	0.26	-
019U0312	3.75	1	0.32	0.245
019U0400	4	1	0.32	0.155
019U0404	4.25	1.25	0.37	-
019U0408	4.5	1.25	0.37	0.255
019U0412	4.75	1.25	0.37	-
019U0500	5	1.25	0.37	0.258



All Keyways are parallel and to British Standard 46: Part 1: 1958, with the exception of those marked\* which are shallower. Where a key is to be used it should be side fitting, with top clearance. Depth of keyway is measured at the CENTRE.

# Fenner®

Reliable | Trusted | Connected