



## DELIDRINK SD LITE

MEETS FDA, EC1935/2004, ADI FREE  
REACH COMPLIANT

### APPLICATION :

- Flexible suction and discharge hose for use in wineries, breweries and other food and beverage industries
- Tasteless and odorless tube with high temperature resistance for open steam sterilization and cleaning (max 30 minutes at 266°F/130°C)
- High resistant EPDM tube resistant against all common cleaning and sanitizing agents.
- Extremely good bending radius
- The special crush-proof design of the hose allows the hose to reshape after accidental compression
- Special low friction cover, wide corrugated and glossy finish, easy to clean

### TEMPERATURE RANGE:

- -40°C to +100°C
  - -40°F to +212°F
- Open end steam cleaning up to 130°C/266°F (max 30 minutes)

### BURST PRESSURE:

- 3:1

### MATERIAL TUBE :

- Mirror smooth, white EPDM rubber compound
- Complies to the most stringent international food regulations
- Non-contaminating formulation
- Excellent for transfer of wine, beer and other alcoholic beverages
- Does not propagate bacteria growth
- Excellent resistance to the most common cleaning agents

### REINFORCEMENTS :

- High tensile spiral-ply textile cords
- Monofilament helix

### MATERIAL COVER :

- Corrugated, red compound, glossy finish
- Easy to clean, low friction material
- Very good abrasion, weather & ozone resistance

### BRANDING:

- White longitudinal Mylar stripe : GOODALL DeliDRINK SD LITE - 10 BAR - 150 PSI
- Embossed strip : GOODALL DeliDRINK SD LITE - FOOD - 10 bar - quarter/year

### STANDARD LENGTHS:

- 40 meter

### DELIDRINK SD LITE

ID		OD		maximum working pressure		Vacuum	minimum burst pressure		minimum bend radius		weight	
mm	inch	mm	inch	bar	psi	%	bar	psi	mm	inch	kg/m	lb./ft.
19	3/4"	35	1,38	10	150	90	30	450	60	2,36	0,74	0,50
25	1"	41	1,61	10	150	90	30	450	75	2,95	0,92	0,62
32	1.1/4"	49	1,93	10	150	90	30	450	90	3,54	1,14	0,77
38	1.1/2"	55	2,17	10	150	90	30	450	120	4,72	1,33	0,89
51	2"	68	2,68	10	150	90	30	450	150	5,91	1,7	1,14