MULTI GREEN



APPLICATION:

- Multipurpose hose for compressed air, water and aqueous solutions
- Suitable for pneumatic tooling
- Conductive tube
- Easy to handle and flexible even at cold temperatures

TEMPERATURE RANGE:

■ -40°C to 100°C for a short time up to +120°C

BURST PRESSURE:

3:1

MATERIAL TUBE :

- Black, smooth EPDM rubber
- Extruded
- Electrically conductive $R \le 10^6 \Omega$

REINFORCEMENTS:

- Polyester yarn, spiralled
- High tensile strength

MATERIAL COVER:

- Green, smooth EPDM rubber compound
- Extruded
- High abrasion, weather and ozone resistance

BRANDING:

■ GOODALL MULTI 20BAR WP (size) MAX.100°C Ω

STANDARD LENGTHS:

Fixed coil lengths

MULTI GREEN

ID	OD	maximum working pressure	minimum burst pressure	minimum bend radius	weight
mm	mm	bar	bar	mm	kg/m
6	13	20	60	40	0,16
10	20	20	60	75	0,34
13	23	20	60	100	0,42
16	26	20	60	125	0,48
19	29	20	60	155	0,55
25	37	20	60	205	0,87

All data at 20° C

MULTI • 20 BAR WP DN 6 MAX. 100°C Ω

All information contained on this datasheet is subject to change without prior notice. GOODALL MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Buyer/end-user is responsible for determining whether the Goodall product is fit for a particular purpose and suitable for buyer's/user's method of use or application. Failure to follow procedures for selection, installation, care, maintenance and storage of hoses may result in the hose's failure to perform properly and may result in damage to property and/or serious injury. Goodall or any of its affiliates or subsidiaries shall not be subject to and disclaims any obligations or liabilities (including but not limited to all consequential, incidental and contingent damages) arising from tort claims (including without limitation negligence and strict liability) or other theories of law.