

## SUPER-CORD



### APPLICATION :

- Extra heavy duty water hose for tough applications in industry, agriculture and construction sites
- Suitable for oil-laden air

### TEMPERATURE RANGE :

- -30°C to +85°C

### BURST PRESSURE:

- 3:1

### MATERIAL TUBE :

- Black, smooth synthetic NBR/SBR rubber
- Suitable for oil-laden air

### REINFORCEMENTS :

- High tensile, spiral-plied textile cords

### MATERIAL COVER :

- Black, synthetic CR rubber compound
- Smooth with cloth impression
- Weather and ozone resistant

### BRANDING:

- White longitudinal Mylar stripe: GOODALL SUPER-CORD - WATER 30BAR
- Embossed strip: GOODALL SUPER-CORD – water – 30 bar WP

### STANDARD LENGTHS:

- 40 meter

### SUPER-CORD

ID	OD	maximum working pressure	minimum burst pressure	minimum bend radius	weight
mm	mm	bar	bar	mm	kg/m
13	21	30	90	117	0,29
16	24	30	90	150	0,36
19	28	30	90	175	0,48
25	35	30	90	230	0,61
32	48	30	90	288	1,39
38	56	30	90	342	1,80

Size tolerances according ISO1307 All data at 68°F/20°C

**Goodall** SUPER-CORD • WATER 30 BAR

All information contained on this datasheet is subject to change without prior notice. GOODALL MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Buyer/end-user is responsible for determining whether the Goodall product is fit for a particular purpose and suitable for buyer's/user's method of use or application. Failure to follow procedures for selection, installation, care, maintenance and storage of hoses may result in the hose's failure to perform properly and may result in damage to property and/or serious injury. Goodall or any of its affiliates or subsidiaries shall not be subject to and disclaims any obligations or liabilities (including but not limited to all consequential, incidental and contingent damages) arising from tort claims (including without limitation negligence and strict liability) or other theories of law.