



TANKER SD FLEXOLINE

APPLICATION :

- Suction and delivery hose for hydrocarbon fuels and mineral oils having an aromatic content of maximum 55% by volume
- Transfer hose used in tank truck and general industrial applications
- The special construction of the hose makes it very light, extreme flexible and easy to handle.
- Electrical static charge can be safely conducted through the hose wall: Ω/T

TEMPERATURE RANGE :

- -40°C to +80°C
- -40°F to +176°F

BURST PRESSUR :

- Minimum 4:1

MATERIAL TUB :

- Black NBR rubber compound
- Electrically conductive R < 10⁶ Ω

REINFORCEMENTS :

- High tensile spiral-plied textile cords
- Steel helix wire

MATERIAL COVER :

- CR rubber compound, black
- Oil, abrasion, weather & ozone resistant
- Wrapped finish impression

BRANDING :

- Yellow longitudinal Mylar stripe : GOODALL TANKER SD FLEXOLINE • OIL 10 BAR – 150 PSI Ω/T
- Embossed strip : GOODALL TANKER SD FLEXOLINE – NBR – SD – 10 bar (150PSI)- Ω/T - quarter/year

STANDARD LENGTHS :

- 61 meter
- 200ft

TANKER SD FLEXOLINE

ID		OD		maximum working pressure		minimum burst pressure		vacuum	minimum bend radius		weight	
nominal bore	inch	mm	inch	bar	psi	bar	psi	%	mm	inch	kg/m	lb./ft.
19	3/4	29	1.14	10	150	40	600	100	76	3.00	0,61	0.41
25	1	35	1.38	10	150	40	600	100	100	3.94	0,76	0.51
32	1 1/4	42	1.65	10	150	40	600	100	120	4.72	0,89	0.60
35	1 3/8	45	1.77	10	150	40	600	100	140	5.50	0,8	0.66
38	1 1/2	48	1.89	10	150	40	600	100	152	5.98	1,04	0.70
40	1 9/16	50	1.97	10	150	40	600	100	160	6.25	1,09	0.74
42	1 5/8	52	2.05	10	150	40	600	100	168	6.75	1,15	0.78
45	1 3/4	55	2.17	10	150	40	600	100	180	7.00	1,22	0.82
48	1 7/8	58	2.28	10	150	40	600	100	192	7.50	1,28	0.87
51	2	61	2.40	10	150	40	600	100	204	8.03	1,34	0.90
60	2 3/8	72	2.83	10	150	40	600	100	240	9.50	2,02	1.36
63	2 1/2	75	2.95	10	150	40	600	90	252	9.92	2,10	1.41
76	3	88	3.46	10	150	40	600	90	304	11.97	2,51	1.69
90	3 1/2	104	4.09	10	150	40	600	90	360	14.00	3,14	2.12
102	4	116	4.57	10	150	40	600	90	408	16.06	3,49	2.35
127	5	145	5.71	10	150	40	600	90	508	20.00	5,93	3.98
152	6	170	6.69	10	150	40	600	80	608	23.94	7,34	4.93

Size tolerances according ISO1307 All data at 68°F/20°C



All information contained on this datasheet is subject to change without prior notice. GOODALL MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Buyer/end-user is responsible for determining whether the Goodall product is fit for a particular purpose and suitable for buyer's/user's method of use or application. Failure to follow procedures for selection, installation, care, maintenance and storage of hoses may result in the hose's failure to perform properly and may result in damage to property and/or serious injury. Goodall or any of its affiliates or subsidiaries shall not be subject to and disclaims any obligations or liabilities (including but not limited to all consequential, incidental and contingent damages) arising from tort claims (including without limitation negligence and strict liability) or other theories of law.