

LABEL OFF 50 SUPER

For easy removal of self-adhesive labels.

1. GENERAL DESCRIPTION

Label remover for quick removal of self-adhesive paper labels and sticky residues. Highest dissolving power.

2. FEATURES

- SOLVENT 50 SUPER is a highly effective solvent mixture for quick removal of self-adhesive paper labels. It penetrates the label paper and loosens the adhesive, so that labels can be easily removed in one go after a short exposure time.
- The spray is equipped with a spray tube and a dispensing brush. The brush allows for exact dosing, ideal for smaller labels.

3. APPLICATIONS

Ideal wherever the removal of adhesive labels is a problem.

- Office equipment
- Address and production stickers
- Identification labels on shelves, drawers or containers
- Labels on spare parts and tools
- Price indicating labels
- Laboratory labels on flasks and bottles

SOLVENT 50 SUPER is very good at dissolving many sticky substances. It is therefore ideal for removing tree resin, chewing gum and tar. Also adhesive remains following the removal of a label, can be dissolved and wiped off.

4. DIRECTIONS

Spray labels generously with SOLVENT 50 SUPER. Most labels can be pulled off after approx. 2 minutes. In difficult cases waiting time can be extended to approx. 15 minutes. If adhesive is still stuck to the substance after the label has been removed, spray SOLVENT 50 SUPER on a (paper) cloth and wipe off the adhesive residue.

Optionally attach a spray tube or a dispensing brush for precise application of SOLVENT 50 SUPER.

TECHNICAL DATA SHEET 2/2

LABEL OFF 50 SUPER

If SOLVENT 50 SUPER is used on plastics or varnished surfaces it is essential to carry out a resistance test before use. The label remover is not suitable for objects made of polystyrene or polycarbonate.

SOLVENT 50 SUPER is a powerful degreasing agent. If it is to be used in large quantities, appropriate protective gloves against skin irritations should be worn. The work area should be well ventilated. As a spray SOLVENT 50 SUPER is highly flammable, the bulk product is flammable. Machinery and working areas must be equipped accordingly.

A safety data sheet (SDS) according to EU directive 97/112 is available for all CRC products.

5. TYPICAL PRODUCT DATA

Smell	:	fruity and fresh
Density at 20°C (FEA 605)	:	0.79g/cm ³
Flashpoint (ASTM D56)	:	<0°C
Evaporation rate (ether = 1) (DIN 53170)	:	94

6. PACKAGING

Aerosol : 200 ml

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com.

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

Version : 4.1

Date: 6 November 2021



CRC INDUSTRIES EUROPE BV
Touwslagerstraat 1 - 9240 Zele, Belgium
Tel. +32 (0)52456011 - Fax. +32 (0)524500341
www.kontaktchemie.com