

Declaration of Compliance

Product/material **CLIPPERLON 2135 FG**

Date of declaration 20-6-2019

To European legislation **EC 1935/2004 EU 10/2011**

To FDA regulation **CFR 21§177.1550**



We confirm that the above mentioned material is compliant to the above mentioned regulations and legislations.

Products from this material are intended for repeated use in contact with the below listed type of foods.

This material has been evaluated according to the requirement of the of the Regulation EC 1935/2004, Annex I. Materials intended to come into contact, directly or indirectly, with food.

The safety of this material has been verified by testing against the migration requirements as described in EU 10/2011 and in accordance with EN1186.

This material has been tested following the FDA regulation on extraction.

ERIKS guarantees that all products of this material are produced according the directive for GMP (Good Manufacturing Practice) 2023/2006/EC, which is part of the guideline EC 1935/2004.

The traceability of the products derived from this material is secured and the regulations for documentation and labelling protocol have been fulfilled.

Migration test results EU 10/2011 (EN1186) - test performed on base material

| Simulant | Simulant media | Type of food | Time/temperature | Ratio S/V |
|----------|----------------|--------------------------|------------------|-----------|
| A | 10% Ethanol | Aqueous food | 4 hours at 100°C | 6 |
| B | 3% Acetic acid | Acidic food with pH <4,5 | 4 hours at 100°C | 6 |
| D2 | Olive Oil | Free fat on the surface | 2 hours at 175°C | 6 |

Extraction test results CFR 21§177.1550

| Test | Requirements |
|-------------------------------------|-----------------------------|
| Extraction in ethyl acetate 2 hours | Max. 3,1 mg/dm ² |
| Extraction in demi-water 2 hours | Max. 3,1 mg/dm ² |
| Extraction in n-heptane 2 hours | Max. 3,1 mg/dm ² |
| Extraction in ethanol 50% 2 hours | Max. 3,1 mg/dm ² |

For more information phone +31 72 514 15 14 or E-mail info@eriks.nl

This declaration is not intended as technical documentation, the suitability of this product for a specific application should be verified with ERIKS.

This declaration is valid until revocation or renewal.

ERIKS bv | P.O. Box 280 | 1800 BK ALKMAAR, The Netherlands | T +31 72 5141514 | E info@eriks.nl | www.eriks.com