

SHOWA

**257**

Foam nitrile palm coating over spandex liner reinforced with stainless steel and aramid

### [ FEATURES

- 13 gauge plated-knit spandex liner with aramid & stainless steel
- Foamed flat dipped coating with sponge finish for good grip
- EN 388:2016: Cut Level F
- ANSI/ISEA 105-16: Level A7 (minimum 4000g)
- Contact Heat level 2
- Lightweight, flexible liner with elastic knitted wrist
- Seamless knit & breathable open back design

### [ BENEFITS

Surprisingly soft and flexible glove engineered with stainless steel & aramid to withstand the highest level of cuts & lacerations

- Exceptional performance against cuts & lacerations due to superior blend of aramid & stainless steel - EN 388 level F and ANSI level A7
- Foam nitrile coating protects palm & fingers from abrasions, snags & punctures, while offering optimum grip in both dry & oily applications
- Plated-knit liner avoids scratchy fibres touching the skin, ensuring a comfortable glove for long lasting wear
- Excellent dexterity thanks to flexible properties of spandex
- Lightweight, breathable liner with open back design reduces sweat and keeps hands dry
- Ergonomically designed to replicate the hand's natural curves
- Launderable for re-use, leads to less waste and cost efficiency

### [ INDUSTRY



**Automotive**



**Construction**



**Glass**



**Manufacturing**



**Mechanical**



**Metallurgy**

### [ IDEAL APPLICATIONS

- Automotive repairs & maintenance
- Mechanical and engineering
- Glass & window handling
- White goods
- Dry & oily parts assembly
- Component Assembly
- Mounting & dismantling



### MATERIAL

- Stainless steel
- Aramid knit
- Spandex

### COATING

- Foam nitrile



### NORMS



SHOWA

**257**



**PACKAGING**

- 12 Pair per polybag
- 6 Polybags per case
- 72 Pair per case



**SIZES**

- S
- M
- L
- XL
- XXL



**COLOUR**

- Black/yellow



**[ YOU MIGHT ALSO BE INTERESTED IN**

SHOWA  
**250**



**MATERIAL**

Aramid knit

**COATING**

Sponge nitrile

**CATEGORY**

Cut

**[ USER INSTRUCTIONS**

Do not use where there are chemical, electrical, thermal or entanglement risks. Wash at 40°C max. Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions. The performance levels apply to the coated surface only. Store in a dry place, away from the light.

**[ DISCLAIMER**

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

**Get in touch**

SHOWA International | WTC - Tower I - Strawinskyaan 1817 - 1077 XX Amsterdam - The Netherlands

[showagroup.eu](http://showagroup.eu) | [info@showagroup.eu](mailto:info@showagroup.eu)

© SHOWA Group 2018 | All rights reserved