

tesa® 4665

Clear cloth tape for outdoor applications

tesa® 4665 is a special outdoor transparent cloth tape. It consists of a 95 µm UV treated polyethylene foil and a 30 mesh woven PET/cotton fabric backing coated with a synthetic rubber adhesive.

tesa® 4665 is a special cloth tape used for different applications where long term, outdoor stability and transparency are needed.

Features:

- At least 1 year outdoor resistant after application (based on accelerated weathering conditions simulation)
- Transparent backing for (almost/nearly) invisible repairs
- Fast and easy applicable
- Hand tearable
- Conformable to complex shapes
- No unpleasant smell
- No sticky sides

Main Application

- Longterm outdoor applications (up to 1 year)
- Heavy duty packaging of outdoor exposed goods
- Quick repairs and seals
- Patching of hosepipes

Technical Data

▪ Backing material	PE extruded cloth	▪ Tensile strength	43 N/cm
▪ Total thickness	215 µm	▪ Temperature resistance (30 min)	95 °C
▪ Type of adhesive	synthetic rubber	▪ UV-resistance	52 weeks
▪ Adhesion to steel	9 N/cm	▪ Mesh	30 count per square inch
▪ Elongation at break	27 %		

Properties

- | | | | |
|-----------------------|-----|-----------------------|-----|
| ▪ Hand tearability | ●●● | ▪ Abrasion resistance | ●●● |
| ▪ Straight tear edges | ●●● | ▪ Water resistance | ●●● |

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=04665>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.