

tesa® 4288

Medium duty tensilised strapping tape

tesa® 4288 is an extremely stable, medium duty polypropylene strapping tape with a natural rubber adhesive system.

tesa® 4288 exhibits high tensile strength with low elongation at the same time. The applied product is highly heat- and cold-resistant, due to the black backing extremely resistant to UV-light.

Main Application

Bundling of copper, iron and plastic pipes; palletising, unitising and coil tabbing.

Technical Data

▪ Backing material	MOPP	▪ Adhesion to steel	5 N/cm
▪ Total thickness	114 µm	▪ Elongation at break	35 %
▪ Type of adhesive	natural rubber	▪ Tensile strength	300 N/cm

Properties

▪ Residue free removal	yes	▪ No discolouration	yes
------------------------	-----	---------------------	-----

For latest information on this product please visit <http://l.tesa.com/?ip=04288>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.