

tesa® 4661

Standard acrylic coated cloth tape

tesa® 4661 is a strong acrylic coated cloth tape. It is based on a 148 mesh woven rayon fabric backing and a natural rubber adhesive.

tesa® 4661 is an all-round cloth tape for a wide range of applications, often used for belting of components.

Features:

- high adhesion, even on rough surfaces
- very high tensile strength
- abrasion-resistant
- available in 7 colors: black, white, grey, yellow, blue, red, green

Main Application

- Marking of wires and cables
- Bundling of pipes, profiles etc.
- Noise and scrub protection
- Harnessing
- Colour coding
- Securing of sharp edges
- Sealing of cartons, tins and tubes
- Belting of components, nails, screws, bicycle, rims etc.
- Floor marking
- Sandblasting
- Floor coating

Technical Data

▪ Backing material	acrylic-coated cloth	▪ Elongation at break	12 %
▪ Total thickness	300 µm	▪ Tensile strength	100 N/cm
▪ Type of adhesive	natural rubber	▪ Temperature resistance (30 min)	140 °C
▪ Adhesion to steel	5.8 N/cm	▪ Mesh	145 count per square inch

Properties

▪ Hand tearability	●●●●	▪ Available as Spools	yes
▪ Straight tear edges	●●●●	▪ Abrasion resistance	●●●●
▪ Easy to remove	yes	▪ Water resistance	●●●
▪ Easy to write on	yes		

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=04661>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.