# productinformation

## tesa® 4934

## Double-sided fabric tape

tesa® 4934 is a double-sided tape. It consists of a fabric backing with a thick, tacky adhesive coating. The synthetic rubber adhesive is solvent free.

tesa® 4934 is a general purpose mounting tape.

tesa® 4934 is easily hand tearable.

## Main Application

Due to the flexible fabric backing and the high coating weight it is particularly suited for mounting on rough, fibrous surfaces, for example carpet laying.

#### Technical Data

Backing material	cloth	Elongation at break	20 %
Color	white	Tensile strength	35 N/cm
Total thickness	200 μm	Type of liner	glassine
Type of adhesive	synthetic rubber		

#### Adhesion to

Steel (initial)	14.5 N/cm	Steel (after 14 days)	24.0 N/cm
PE (initial)	8.0 N/cm	PE (after 14 days)	8.5 N/cm
PP (initial)	16.0 N/cm	PP (after 14 days)	24.5 N/cm
PVC (initial)	14 0 N/cm	PVC (after 14 days)	22.5 N/cm

### **Properties**

Temperature resistance short term	60 °C	Static shear resistance at 23°C	••••
Temperature resistance long term	40 °C	Static shear resistance at 40°C	•••
Tack	•••	Static shear resistance at 70°C	•
Ageing resistance (UV)	• •	Fogging	•••
Humidity resistance	•••		

Evaluation across relevant tesa® assortment: •••• very good ••• good •• medium • low

Dags 1 of 1 - As of 05 /05 /019

For latest information on this product please visit <a href="http://l.tesa.com/?ip=04934">http://l.tesa.com/?ip=04934</a>