productinformation

tesa® 51007

PET cloth tape for abrasion protection

tesa® 51007 is a PET cloth wire harness tape with a rubber based adhesive.

Major Features:

- High temperature resistance 150°C/3000h
- Abrasion resistant
- Strong adhesion

Color: Black

Main Application

tesa® 51007 is designed for the engine compartment, providing abrasion protection. Specifically made for automatic bundling

Technical Data

	Backing material	PET cloth	Temperature resistance (3000h)	150 °C
	Total thickness	320 μm	Abrasion resistance (10mm	Class C (acc. to
	Type of adhesive	rubber based	mandrel)	LV312)
•	Adhesion to steel	4.5 N/cm	Abrasion resistance (5mm	Class B (acc. to
	Elongation at break	22 %	mandrel)	LV312)
	Tensile strength	175 N/cm	Flame resistance as composite	Class B (acc. to
•	Temperature resistance min.	-40 °C		LV312)
			Unwind force (roll width ≤ 9mm)	6 N/roll (30 m/min)
			Unwind force (roll width > 9mm)	6 N/roll (30 m/min)
			Noise damping (decibel)	Class A (acc. to

Additional Information

Standard widths: 9, 19, 25, 32 mm

Standard lengths: 50 m

- Most combinations of width and length are possible
- Further dimensions are available upon request
- Standard core diameter: 76 mm
- Applicable for red ring assembly aid

age 1 of 1 - As of 01/02/2018

For latest information on this product please visit http://l.tesa.com/?ip=51007

LV312)