

MASKING TAPE +

THORMAS 2017-01

THORMAS General Purpose Masking Tape is a multipurpose tape that is suitable for any type of paint for application in building and construction.

APPLICATION

- All in-door painting processes

FEATURES

- Temperatures resistance up to 60°C (60 mins)
- No residue
- Adaptable to irregular surfaces
- Compatible with solvent and water based paint
- Smooth unwind
- Sharp paint lines

STORAGE AND CARE

THORMAS tapes must be stored in a dry location, protected from direct sunlight exposure and from freezing. Storage temperatures should be as close as possible to room temperature; suggested storage temperature should range from 15 to 25°C with max. relative humidity of 60%.

Make sure the surface you wish to place the tape on is cleaned, dried and free from oil and dust. It is suggested not to apply the tape with temperatures lower than 10°C. With a storage temperature lower than 10°C, it is always suggested temperature reconditioning of the tape at room temperature (15°C - 25 °C) before its use.

INDUSTRIES



building



construction



DIY

ARTICLE NR	WIDTH (MM)	LENGTH (M)	MAX TEMP. RESISTANT		WEIGHT (G/M ²)	THICKNESS (µM)	DIKTE (µM)	TAPE COLOR	QUALITY
			30 MIN	60 MIN					
3220040	19	50	60°C	60°C	90	120	120	Off white	+
3220041	25	50	60°C	60°C	90	120	120	Off white	+
3220042	38	50	60°C	60°C	90	120	120	Off white	+
3220043	50	50	60°C	60°C	90	120	120	Off white	+