

# MASKING TAPE ++

THORMAS 2017-01

**THORMAS Temperature Resistant Masking Tape is aptly suited for any type of paint for application in automotive, construction, work sites and industrial sectors.**

## APPLICATION

- All in-door painting processes

## FEATURES

- Temperatures resistance up to 80°C (60 mins)/ 90°C (30 mins)
- No residue
- Adaptable to irregular surfaces
- Compatible with solvent and water based paint
- Removal without breaking
- Smooth unwind
- Crepe paper backing
- Sharp paint lines

## STORAGE AND CARE

THORMAS tapes must be stored in a dry location, protected from direct sunlight exposure and from freezing. Storage temperatures should be as close as possible to room temperature; suggested storage temperature should range from 15 to 25°C with max. relative humidity of 60%.

Make sure the surface you wish to place the tape on is cleaned, dried and free from oil and dust. It is suggested not to apply the tape with temperatures lower than 10°C. With a storage temperature lower than 10°C, it is always suggested temperature reconditioning of the tape at room temperature (15°C - 25 °C) before its use.

## INDUSTRIES



building



construction



MRO



automotive



marine



aerospace

ARTICLE NR	WIDTH (MM)	LENGTH (M)	MAX TEMP. RESISTANT		WEIGHT (G/M <sup>2</sup> )	THICKNESS (µM)	DIKTE (µM)	TAPE COLOR	QUALITY
			30 MIN	60 MIN					
3220044	19	50	80°C	90°C	92	125	125	Off white	++
3220045	25	50	80°C	90°C	92	125	125	Off white	++
3220046	38	50	80°C	90°C	92	125	125	Off white	++
3220047	50	50	80°C	90°C	92	125	125	Off white	++