

EN 854 3TE

TFE03TEI



APPLICATIONS :



APPLICABLE SPECIFICATIONS

EN 854 3TE

Braided hose textile.

Inner tube: Oil resistant synthetic rubber.

Reinforcement: Textile braids.

Coverage: Synthetic rubber resistant to oils, fuels and atmospheric conditions.

Recommended fluids: Biological and mineral oils, glycol-water based, water, lubricants.

working temperature: from -40 to +100° C petroleum based fluids, from -40 to +70° C for water based fluids, from 0 to +70°C water.

Product number	ID		Dimension	OD	Max WP		Min BP		Min BR		Weight (approx)		Ferrule
	mm	in	dash size		bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFE03TEI03	4.8	3/16"	03	12.8	160	2320	640	9280	40	1.575	0.200	0.134	0003-03
TFE03TEI04	6.4	1/4"	04	14.4	145	2103	580	8410	45	1.772	0.234	0.157	0003-04
TFE03TEI05	8	5/16"	05	16.9	130	1885	520	7540	55	2.165	0.305	0.205	0003-05
TFE03TEI06	9.5	3/8"	06	18.5	110	1595	440	6380	70	2.756	0.352	0.237	0003-06
TFE03TEI08	12.7	1/2"	08	21.7	93	1349	372	5394	85	3.346	0.435	0.292	0003-08
TFE03TEI10	16	5/8"	10	25.9	80	1160	320	4640	105	4.134	0.575	0.386	0003-10
TFE03TEI12	19	3/4"	12	29	70	1015	280	4060	130	5.118	0.625	0.420	0003-12
TFE03TEI16	25.4	1"	16	35.9	55	798	220	3190	150	5.906	0.855	0.575	0003-16