

## Orange Star

### ISO 3821:2019



#### Application:

- A flexible hose for transporting propane and butane (LPG), for CNG, methylacetylene and propadiene mixes (MPS).
- For welding and cutting.

#### Temperature range:

- -30°C to +70°C

#### Burst pressure:

- 3:1

#### Material tube:

- Black, smooth EPDM rubber
- Extruded
- Gastight

#### Reinforcements:

- Textile, spiralled
- High tensile strength

#### Material cover:

- Orange, smooth EPDM rubber
- Extruded
- Weather and ozone resistant

#### Standard lengths:

- 50 meter

I.D.	O.D.	Maximum working pressure	Minimum burst pressure	Minimum bend radius	Weight
mm	mm	bar	bar	mm	kg/m
6,3	13,3	20	60	40	0,14
8	14	20	60	40	0,13
8	15	20	60	40	0,18
9	16	20	60	45	0,20
10	17	20	60	50	0,21
12,5	22,5	20	60	65	0,36

Size tolerances according ISO 1307

Tested according ISO 1402

**Date** 26/02/2022  
**Revision** 000

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.