



DELIDRINK SD

MEETS FDA, EC1935/2004, ADI FREE
REACH COMPLIANT

APPLICATION :

- Flexible suction and discharge hose for use in wineries, breweries and other food and beverage industries
- Tasteless and odorless tube with high temperature resistance for open steam sterilization and cleaning (max 30 minutes at 266°F/130°C)
- High resistant EPDM tube resistant against all common cleaning and sanitizing agents.
- Extremely good bending radius
- Special low friction cover, wide corrugated and glossy finish, easy to clean

TEMPERATURE RANGE:

- -40°C to +120°C
 - -40°F to +250°F
- Open end steam cleaning up to 130°C/266°F (max 30 minutes)

BURST PRESSURE:

- 3:1

MATERIAL TUBE :

- Mirror smooth, white EPDM rubber compound
- Complies to the most stringent international food regulations
- Does not propagate bacteria growth
- Non-contaminating formulation
- Excellent for transfer of wine, beer and other alcoholic beverages
- Excellent resistance to the most common cleaning agents

REINFORCEMENTS :

- High tensile spiral-ply textile cords
- Built-in steel helix

MATERIAL COVER :

- Corrugated, red compound, glossy finish
- Easy to clean, low friction material
- Very good abrasion, weather & ozone resistance

BRANDING:

- White longitudinal Mylar stripe : GOODALL DeliDRINK SD - 10 BAR – 150 PSI
- Embossed strip : GOODALL DeliDRINK SD – FOOD – 10 bar - quarter/year

STANDARD LENGTHS:

- 40 meter

DELIDRINK SD

ID		OD		maximum working pressure		Vacuum	minimum burst pressure		minimum bend radius		weight	
mm	inch	mm	inch	bar	psi	%	bar	psi	mm	inch	kg/m	lb./ft.
63,5	2.1/2"	79,5	3,13	10	150	90	30	450	195	7,68	2,26	1,52
75	3"	91	3,58	10	150	90	30	450	230	9,06	2,96	1,99
100	4"	117	4,61	10	150	90	30	450	300	11,81	3,95	2,65

Size tolerances according ISO1307

All data at 68°F/20°C

Goodall DELIDRINK SD • 10 BAR - 150 PSI



All information contained on this datasheet is subject to change without prior notice. GOODALL MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Buyer/end-user is responsible for determining whether the Goodall product is fit for a particular purpose and suitable for buyer's/user's method of use or application. Failure to follow procedures for selection, installation, care, maintenance and storage of hoses may result in the hose's failure to perform properly and may result in damage to property and/or serious injury. Goodall or any of its affiliates or subsidiaries shall not be subject to and disclaims any obligations or liabilities (including but not limited to all consequential, incidental and contingent damages) arising from tort claims (including without limitation negligence and strict liability) or other theories of law.